

QUARTZ CRYSTALS

MHz range

SMD-version

model	KX - K	
frequency range	3,50 ~ 70,0 MHz	
mode	fundamental, 3 rd overtone	
operating temperature	standard -20° ~ + 70° C available -40° ~ + 85° C (=KX-KT)	
frequency tolerance at +25° C	standard ± 30 ppm, available ± 10 ~ ± 50 ppm	
temperature tolerance at -20° ~ +70° C -40° ~ +85° C	standard ± 50 ppm, available ± 15 ~ ± 50 ppm standard ± 100 ppm, available ± 25 ~ ± 100 ppm	
load capacitance C_L	standard: 16 pF, avail. 12 ~ 30 pF	
series resonance R_1 max.	fundamental	3,5 ~ 3,99 MHz 150 Ohm 4,0 ~ 5,99 MHz 120 Ohm 6,0 ~ 7,99 MHz 80 Ohm 8,0 ~ 9,99 MHz 60 Ohm 10,0 ~ 40,0 MHz 50 Ohm
	3 rd overtone	35,0 ~ 39,99 MHz 100 Ohm 40,0 ~ 49,99 MHz 80 Ohm 50,0 ~ 70,0 MHz 50 Ohm
aging (first year)	± 5 ppm	
shunt capacitance C_0 max.	7,0 pF	
drive level in mW	0,1	
RoHS	started from date code May, 2005	
contents of reel	1000 pcs.	
part no.	12.87800 ~ 12.87899	

